

CANBERRA THEATRE CENTRE

Canberra Theatre

Technical Specifications

Schedule 13

Updated
09/09/2020

The information in the following document was true and correct at the time of printing

**The Canberra Theatre Centre reserves the right to adjust its inventory and specifications
without notice**

Contents

STAFF CONTACTS.....	5
STAGE	6
Auditorium	6
Orchestra Lift / Pit.....	7
Flying Facilities	7
Hanging Plot	8
Access Equipment.....	9
Lifting Equipment	10
Stage Covers	10
Loading Dock	10
Additional Rigging Notes.....	11
Staging Notes.....	11
LIGHTING.....	12
Positions	12
Control.....	12
Dimmer Systems.....	13
House Lights	13
Stage Luminaires	14
Followspots	15
Patching.....	15
Power	16
Cabling.....	16
Atmospherics.....	16
Lighting Notes	16
AUDIO.....	17
Control Points	17
Stage systems	18
Digital Audio Consoles	18
Microphones.....	19
Audio Only Power	20
House Speaker System	20
Control & Amplification	21

AUDIO VISUAL.....	22
Projectors.....	22
Screens	22
Audio Visual Notes.....	23
BACKSTAGE.....	24
Communications.....	24
Dressing Rooms.....	25
Laundry / Wardrobe.....	25
Production Facilities.....	25
Greenroom.....	26
Stage Door.....	26
ADDITIONAL FACILITIES & INFORMATION.....	26

STAFF CONTACTS

Technical Director

Phone Number: 02 6243 5736
Mobile Number: 0420 578459
Email Address: rohan.cutler@act.gov.au

Rohan Cutler

Technical Producer

Phone Number: 02 6243 5780
Mobile Number: 0415 938 330
Email Address: roni.wilkinson@act.gov.au

Roni Wilkinson

Head of Lighting

Phone Number 02 6243 5734
Mobile 049717459
Email Address stefan.wronski@act.gov.au

Stefan Wronski

Head Mechanist

Phone Number 02 6243 5758
Mobile 0411 892542
Email Address loki.clarke@act.gov.au

Loki Clarke

Head of Audio

Phone Number 02 6243 5759
Mobile 0417 015644
Email Address petar.milinkovic@act.gov.au

Petar Milinkovic

Box Office Manager

Phone Number 02 6290 9377
Email Address sam.hardiman@act.gov.au
Fax Number 02 6230 1098

Sam Hardiman

Stage Door

Phone Number 02 6243 5746 (Manned as required)

Venue Address

**Canberra Theatre
Civic Square London Circuit
Canberra ACT 2601**

Venue Postal Address

**Canberra Theatre Centre
PO Box 226
Canberra ACT 2601**

Website:

www.canberratheatrecentre.com.au

STAGE

Brief Stage Description

Unraked stage with a proscenium arch and flying facilities. Hardwood floor covered with Masonite sheets. Screwing into surface permitted but larger holes to be authorised by Head Mechanist.

Stage crossover behind US fly line.

Stage distributed load limit	500kg/m2
Stage point load limit	Not Known
Stage rake	No

Stage Dimensions

Proscenium

Width	16.9m
Height	5.8m

Setting Line

In line with House Curtain

Distance From (SL = Setting Line, CL = Centre Line)

SL to US edge of fire curtain	0.3m
SL to DS edge of apron	2.1m
SL to DS edge of Orchestra Lift/Pit	6.1m
SL to first fly line	220mm
SL to last upstage fly line	10.2m
SL to rear wall	18m
CL to OP wall (or obstruction)	9.8m
CL to PS wall (or obstruction)	18m
Stage to underside of grid	15.7m

Overhead obstructions

Fixed platforms at 7.2m above stage level between 400mm and 1m US of setting line, protruding onto stage at 6.95m from the centre line. Platforms are fixed on both sides of stage. Total distance between the platforms measures 13.9m

Auditorium

Raked single level with central crossover.

Seating capacity with additional
Orchestra lift/pit seating installed **1239**

Seating capacity without
Orchestra lift/pit seating installed **1184**

Orchestra Lift / Pit

Orchestra Lift

A motorised orchestra lift is operational

Set positions for orchestra lift where lift at auditorium level is 0mm

Stage level at **+1000mm** above auditorium.

Orchestra pit level at **-1400mm** below auditorium.

Lift can be set at any height? **Yes - pending CTC approval**

SWL of orchestra lift **3.5 Tonne**

Dimensions of the orchestra pit **4.2m x 15m**

Orchestra pit maximum capacity **45 – 50**

Pit net available **Yes**

Standard pit position is at auditorium level with seating installed

Flying Facilities

Fly System

Single purchase handline system.

Fly System Details

Operating Position	OP at stage level.
Total number of Lines	62
Panorama Lines	2 bars OP, 2 bars PS, electrically winched.
Batten Drift	14m
Batten Type	75x50mm batten.
Batten Length	16m
Batten Extensions	N/A
Batten Pick-ups	4 Pick ups
Batten Point Load	Not Known
Batten W.L.L.	500 kg
Cradle Capacity	340 kg
LX bars can be swung	Yes
Fly bars can be swung	No

SEE HANGING PLOT FOR LINE ALLOCATIONS AND FURTHER INFO

Hanging Plot

SL: Setting Line as indicated previously

Line Type: **SP** = Single purchase, **DP** = Double purchase, **MW** = Motor Winch, **HW** = Hand Winch, **HL** = Handline

S.W.L. = Maximum capacity above bar weight

Line #	Distance from SL	Line Type	S.W.L	Venue Allocation	Intended Use <i>(hiring company use)</i>
HC	0	MW		House Curtain	
1	220	SP	340kg	Pro Border	
2	370	SP	"	Pro Legs	
3	530	SP	"		Short batten to accommodate platforms. 13m length
4	700	SP	"	LX 1	Short pipe to accommodate platforms. 13m length
5					Not available for use
6					Not available for use
7	1150	SP	"		
8	1300	SP	"		
9	1440	SP	"		
10	1600	SP	"		
11	1750	SP	"		
12	1900	SP	"		
13	2050	SP	"		
14	2200	SP	"		
15	2360	SP	"		
16	2500	SP	"	Border	
17	2650	SP	"	Legs	
18	2800	SP	"		
19	2950	SP	"	LX 2	
20	3120	SP	"		
21	3270	SP	"		
22	3420	SP	"		
23	3570	SP	"		
24	3730	SP	"		
25	3880	SP	"		
26	4050	SP	"	Mid Tabs	
27	4200	SP	"		
28	4350	SP	"	Border	
29	4500	SP	"	Legs	
30	4650	SP	"		
31	4800	SP	"	LX 3	
32	4950	SP	"		
33	5100	SP	"		
34	5250	SP	"		
35	5450	SP	"		
36	5600	SP	"		
37	5750	SP	"		
38	5900	SP	"	LX 3a rectangular batten	
39	6050	SP	"		
40	6200	SP	"	Border	

41	6350	SP	"	Legs	
42	6500	SP	"		
43	6650	SP	"	LX 4	
44	6800	SP	"		
45	6950	SP	"		
46	7100	SP	"		
47	7250	SP	"		
48	7420	SP	"		
49	7560	SP	"		
50	7720	SP	"	LX 4a rectangular batten	
51	7880	SP	"		
52	8020	SP	"	Border	
53	8180	SP	"	Legs	
54	8350	SP	"		
55	8550	SP	"	LX 5 Flood Bar	
56	8800	SP	"		
57	8950	SP	"		
58	9100	SP	"		
59	9250	SP	"		
60	9400	SP	"	LX 5a rectangular batten	
61	9600	SP	"		
62	9800	SP	"	Smother	
63	10000	SP	"		
64	10200	SP	"	Cyclorama	

Drapery

*Type	Material	Colour	Width	Height	Quantity
House Curtain	Velour	Blue/Grey	18m	6.9m	1
Borders	Flat Wool	Black	16m	3m	5
Legs	Flat Wool	Black	4m	7.3m	5
Tabs	Flat Wool	Black	16m	7m	2
Smother	Flat Wool	Black	16m	7m	1
Cyclorama	Plastic	Cream white	16.5m	8.2m	1
Scrim	Sharks tooth	Black	16m	6.7m	1
Scrim	Sharks tooth	White	16m	6.7m	1
Panorama Tabs	Flat Wool	Black	10m	10m	2

Access Equipment

Elevated Work Platform

Genie GS-1932, operator driven.

Upright UL-40DC, push around vertical lift.

Tallescope wheeled ladder. 90kg capacity.

Max. platform height 5.8m

Max. platform height 12.2m

Max. platform height 5.9m

Please note the UL-40DC and tallescope units are shared between venues

EWP Restrictions

Outriggers must be used on the Uprights UL-40, and one staff member must be located at the base whilst in use.

Ladders

- 1 x 0.9m aluminium stepladders
- 1 x 1.8m aluminium stepladders
- 1 x 1.8m fibreglass stepladder
- 1 x 3m aluminium stepladder
- 1 x 4.51m x 7.87m aluminium extension ladder.

Staging Units

30 timber rostra with metal scissor action adjustable legs. 1000x 2000 with height adjustable in 200mm increments. (i.e., 200mm, 400mm, 600mm, 800mm, 1000mm)

Lifting Equipment

4 x 1tonne chain motors and control shared between both venues. There is an additional charge for these items, please contact Head Mechanist for pricing and availability.

Stage Covers

Style	Tarkett: Harlequin 'Cascade'
Dimensions	6 rolls of 2m x 15m
Colour	Black

Stage Traps

N/A

Safety Curtain

Safety Curtain installed	Yes
Safety Curtain must be unobstructed at all times	Yes
Thickness of Fire Curtain	200mm
Distance from setting line	300mm DS

Note: Measurement is to the downstage edge of the Fire Curtain.

Additional Requirements

Curtain must remain in the down position whilst venue not in use.

Loading Dock

Access

Truck access via back laneway. Entry to this laneway is via the Northern car park at the rear of the Canberra Playhouse (Theatre Lane).

Loading Dock Height	Street level
Door Dimensions	4.5m High 4.0m Wide

Restrictions / Obstructions

Unloading/loading ramp required. Ramp required if equipment cannot be unloaded with a forklift.

Additional Rigging Notes

Rigging points O.P. and P.S. of orchestra LX bar 500kgs W.L.L.

For further information regarding the weight loading for rigging points over the stage and auditorium, please do not hesitate to contact the Head Mechanist.

The Head Mechanist is only too pleased to answer any questions with regards to rigging.

Staging Notes

All flown items must be rigged with rated equipment and is subject to approval by a venue representative.

There is limited rigging gear available in house. Including lifting straps, FSWR lines, shackles and some pulleys.

Forklift and licensed operator available onsite.

LIGHTING

Positions

Stage LX Bars	All Stage LX bars except for LX 1 can be swung
	LX1 Usable bar width 12m
	All other LX bars usable bar width 13m

See hanging plot for standard LX bar locations

FOH Orchestra Bar

Setting Line to lighting bar	3.8m @ centre, curved to 2.5m at each end
Usable bar width	16m

FOH Concert Bar

Setting Line to lighting bar	10.5m
Height above Stage	8.5m
Usable bar width	5.4m

FOH Bridge #1

Setting Line to lighting bar	15.0m
Height above Stage	9m
Usable bar width	18.6m

FOH Box Booms (PS & OP)

Setting Line to FOH Box	6.5m	<i>(Distances are to the highest downstage point of boom or perch.)</i>
Maximum lanterns per box	8	

See Venue Plans for further information

Control

Available Positions	Control Room, Auditorium, Stage
Lighting console	ETC Gio 8k
Output Parameters	8192 (full spec at www.etcconnect.com)
LD Monitor	Multi screen LD interface
Signal output	DMX 512 (as standard), ArtNet, ETCNet3
Signal distribution	Ethernet Spine, PathPort DMX nodes
Wireless Remote riggers available	Yes

Other consoles available on request:

- 1 x Martin M1 HD
- 1 x ETC Ion

Dimmer Systems

Total Dimmers	373
2.5Kw Dimmer Racks	State Automation SPC/APC/VST
Total dimmers @ 2.5kw per dimmer	333
5Kw Dimmer Racks	State Automation APC
Total dimmers @ 5kw per dimmer	40

Dimmer Locations

Dimmer outlets are distributed throughout the venue. Patch distribution plan available on request.

Several DMX controlled relay modules are available. These may be installed in any location within the dimmer system.

House Lights

Independent control	Yes. With adjustable fade time.
Control positions	Control Room, Prompt Corner, Auditorium Mix Position.

Stage Luminaires

Profiles

Make	Model	Angle	Detail / Accessories	Watt	Numbers	Totals
ETC	Source 4	10	Rigged FOH bridge 4	750	6	6
ETC	Source 4	19	Rigged FOH Bridge 3 to give a 4 colour wash	750	24	40
ETC	Source 4	19	Rigged FOH Bridge 1 as specials	750	6	
ETC	Source 4	19	Store	750	10	
ETC	Source 4	15/30	Rigged FOH Box Booms to give a 4 colour wash	750	16	35
ETC	Source 4	15/30	Store	750	19	
ETC	Source 4	25/50	Store.	750	20	20
ETC	Source 4	26,36,50	Shared between venues. Contact HLX for availability.	750	40 Ea	40 Ea
Selecon	SPX Zoom	15/35	Rigged FOH Bridge 3 specials	800	6	40
Selecon	SPX Zoom	15/35	Rigged FOH Bridge 2 specials	800	8	
Selecon	SPX Zoom	15/35	Rigged 4 on each Stage LX bar specials	800	16	
Selecon	SPX Zoom	15/35	Store	800	10	
ETC	Source 4 Jr Zoom	25/50	6 on each stage perch and flown side ladders	575	60	80
ETC	Source 4 Jr Zoom	25/50	4 on each LX bar incl. Orchestra Bar (Break up gobo wash)	575	20	

Fresnels

Make	Model	Detail / Accessories	Watt	Numbers	Totals
Selecon	Rama	Rigged Orchestra bar to give a 5 colour wash incl. o/w	1000	20	60
Selecon	Rama	Rigged 5 on each LX bar for an o/w wash	1000	20	
Selecon	Rama	Store	1000	20	
Selecon	Arena	Rigged 8 on each LX bar to give a 4 colour wash (High side cross)	2000	32	40
Selecon	Arena	Store	2000	8	
		Barn doors available for all the above.			

PCs

Make	Model	Detail / Accessories	Watt	Numbers	Totals
Selecon	Rama	Store. Barn doors available.	1000	20	20

Par Cans

Make	Model	Angle	Detail / Accessories	Watt	Total
Generic	PAR 64	MFL	240V	1000	24*
* Please check with the Head Electrician for availability as these lamps are no longer manufactured					

CYC Wash

Make	Model	Detail / Accessories	Watt	Numbers	Total
Altman	Spectra CYC200	LED RGBA 10 channel Flood Bar (line 55)	480	7	20
Altman	Spectra CYC200	LED RGBA 10 channel Ground Row	480	7	
Altman	Spectra CYC200	Store	480	6	
Ianaro	Pallas 4 cell	Store	750	16	16
Selecon	Cyc 4 cell	Store	800	10	10

Followspots

Make	Model	Angle	Detail / Accessories	Watt	Total
Selecon	Performer	5/9	6 colour magazine	1200	2
Robert Juliat	Aramis	4.5/8	6 colour magazine + CTO + Frost Mechanical dimmer	2500	2

Additional Lighting

Item	Make	Model	Detail / Accessories	Watt	Total
Intelligent luminaires	Robe	Robin 800 wash	Shared between venues	LED 700	16
	Robe	DL4X spot	Shared between venues	LED 700	8
2 way LED Molefay	ShowPro	Blinder II	Shared between venues	LED 156	4
4 way LED Molefay	ShowPro	X-Blinder	Shared between venues	LED 300	4
RGBW LED Par	Martin	Rush Par 2	Shared between venues	LED 152	22

Patching

Location	Quantity	Numbering	Detail / Accessories
Rear FOH			CCT bar 8 circuits to Concert Bar Patch
PS FOH Bridge 1			CCT bar 12 circuits to Concert Bar Patch
CS FOH Bridge 1			CCT bar 12 circuits to Concert Bar Patch
OP FOH Bridge 1			CCT bar 12 circuits to Concert Bar Patch
CS Concert bar	43	1 – 43	CCT bar 16 circuits to Concert Bar Patch
CS FOH Orchestra bar	18	44 – 61	CCT bar 40 circuits to Orchestra Bar Patch
PS FOH Box boom	8	62 – 69	
OP FOH Box boom	8	70 - 77	
PS Pit Wall	1	78 - 84	
OP Pit Wall	1	85	
PS Fly Floor		86 - 229	Flown Spot bars numbered from D/S 222 – 229 20Amp sockets 1 x 20Amp hot power US
PS Lighting Bridge	20	230- 249	230 – 237 paired with Perch bar on tormentor
PS DS above floor	4	250 - 253	Situated low to the stage floor (not a well)
OP Lighting bridge	20	254 - 273	254 – 261 paired with Perch bar on tormentor
OP DS above floor	4	274 - 277	Situated low to the stage floor (not a well)
OP fly floor US	10	278 - 287	
US OP wall	6	288 - 293	
PS Stage Floor Wells	30	294 - 323	5 wells – 6 per well
OP Stage Floor Wells	30	324 - 353	5 wells – 6 per well
US PS Stage Well	4	354 - 357	20 Amp sockets -1 x 20Amp hot power
US OP Stage Well	4	358 - 361	20 Amp sockets - 1 x 20Amp hot power
US PS Fly floor	8	362 - 369	4 x 10 Amp sockets per dimmer 6m above stage level
Rear wall	4	369 - 373	20 Amp sockets

Power

3 Phase Outlets

- 3 x 40 amp 3phase outlets DS PS (8m from acting area)
- 3 x 40 amp 3phase outlets US OP (5m from acting area)
- 2 x 40 amp 3phase outlets US OP Basement (10m from Orchestra Pit)
- 2 x 40 amp 3phase outlets PS fly floor (6m above stage level)

Power Lock

- 100 amp 3 phase supply available on PS Fitted with Power Lock sockets (other wiring formats require licensed electrician to wire in)
- 250 amp 3 phase supply available on OP Fitted with Power Lock sockets (other wiring formats require licensed electrician to wire in)

Cabling

240v Extension Cable

- 100 x 10m
- 50 x 7m
- 50 x 5m

Looms

- 10 x 4-way at 15m

3 phase Extensions

- 4 x 20m Shared between venues.

Atmospherics

- | | |
|------------------------------------|---|
| 1 x MDG ATMe haze machine | DMX and stand-alone function available |
| 1 x Rosco 1600 fog machine * | DMX and stand-alone function available |
| 2 x Martin Jem Compact Hazer Pro * | DMX and stand-alone function available |

Please note there is an additional hire charge associated with these products. Please contact the Head of Lighting for more information

**These products are shared between venues. Please check with Head of Lighting for availability*

Lighting Notes

- FOH standard rig gives an excellent front 4-colour wash
- 10 x 2m five rung wheeled floor ladders available (1 lantern per rung)
- The ladders are extendable to 4m with attachable pipe.
- On stage spot bars have 24 circuits each and are generally 13m in length

AUDIO

Control Points

Control Room	Yes	
Location Detail	Bio box	2.5m x 2m
Tie Lines to stage	Yes	x 20
Auditorium	Yes	
Location Detail	Centre mid rear	

Default hold

Seats X, Y 16-27, W 20-27 and ZA 16-26.

Row W is held for to accommodate console overhang.

Row ZA is held if sightlines are impaired over the console

6m x 1.7m (X&Y 16-27). **Total 43 seats**

Typical hold

Seats X, Y 20-27 and ZA 21-24.

Row ZA is held if sightlines are impaired over the console.

4m x 1.7m (X&Y 20-27). **Total 16-20 seats**

Sound hold Connections to prompt corner.

- **36** x analogue male XLR inputs from prompt corner.
- **16** x analogue female XLR feeds to prompt corner.
- **4** channels of coms connections to SM console.
- **6** lines of cat 6A to prompt corner.
- **4** lines of rg56 suitable for SDI, MADi and AVID connections to prompt corner.

Cross stage Audio patch Prompt to OP corner.

- **20** x XLR line 16 male and 4 female at prompt end.
- **2** x cat 6A lines.
- **2** x SDI/MADI lines.

Up stage Audio patch Prompt to back stage centre.

- **4** x cat 6A lines.
- **2** x SDI/MADI lines.
- **2** x analogue XLR lines.

Stage systems

Radial Engineering 56-Channel Convertible V12 Snake System

- 56 x XLR inputs
- 3 x outputs (1 x Direct, 2 x Transformer Isolated) with cables (XLR Tails)
- 5 x 12-Way input patch
- 10 x 12-input stage boxes
- 5 x 15 metre sub-snakes
- 5 x 30 metre sub-snakes

Additional sub-snakes and stage boxes may be available on request

Multicore hard-wired stage drops

- 1 x 20m (8 XLR Male Tail to 8 XLR Female Stage Box)
- 1 x 20m (12 XLR Male Tail to 12 XLR Female Stage Box)
- 1 x 30m (8 XLR Male Tail to 8 XLR Female Stage Box)
- 1 x 30m (12 XLR Male Tail to 12 XLR Female Stage Box)

Cables

XLR Cables (Various lengths- please advise quantity required)

Note: Stage systems and cables are shared across venues. Please check on availability.

Digital Audio Consoles

DiGiCo consoles. See <http://www.digico.biz/>

DiGiCo SD8 (Stealth Core 2, software version 12.2.1280) + **Madi-Rack** (48 Inputs + 16 Outputs. Note: Madi-Rack is limited to 48kHz Operation)

DiGiCo SD9 (Stealth Core 2, software version 12.2.1280) + **D-Rack** (32 Inputs + 8 Outputs)

DiGiCo SD11 (Stealth Core 2, software version 12.2.1280) + **D-Rack** (32 Inputs + 8 Outputs)

Yamaha consoles.

See <http://www.yamahaproaudio.com/global/en/products/mixers/>

Yamaha M7CL-32

Yamaha DM1000

Note: Mixing consoles are shared across venues. Please check on availability.

Playback

Item	Make	Model	Detail	Total
CD player	Denon	DN-C680	Single CD player	2
MD player	Denon	DN-M1050R	Single Minidisc player/recorder	2
File player	Denon	DN-F650R	USB/SD wav/mp3 recorder/player	1
USB DI	ARX	USB DI	Computer USB audio interface	2
USB DI	Radial	USB-Pro		2

Accessories

Item	Model	Detail / Accessories	Total
Microphone stands	Round base	Straight	8
Microphone stands	Tri base	Boom arm tall	24
Microphone stands	Tri base	Boom arm short	16

Speaker Patching

Location	Quantity	Numbering	Detail
Redundant speaker patching available on XLR	12	NA	PC to various stage points

Microphones

Make	Model	Detail / Accessories	Use	Total
Shure	Beta 87A	Clips	Vocals	4
Shure	Beta 58A	Clips	Vocals	6
Shure	SM58	Clips	Vocals	2
Shure	SM58S	Switched	Shout/Announce	4
Shure	SM57	Clips	Instruments	8
Shure	B91	all	Instruments	1
Shure	B98	all	Drums	4
AKG	CK93	Clips	Instruments	4
AKG	CK98	Clips	Distance miking	2
AKG	SE300B	Clips	Preamp for 93/98	6
AKG	C451B	Clips	Instruments	6
AKG	C414	Clips	Various	4
Neumann	KM184	Clips	Instrument	8
Beyer	M88	Clip	Instrument	1
Sennheiser	E604	Claw	Percussion	4
Sennheiser	E906	Clips	Instrument	2
Sennheiser	MD421	Clips	Instrument	4
Audix	D6	Clips	Kick drum	2
Audio Technica	AE2500	Clips	Kick Drum	1
Crown	PCC160 PZM	-	Boundary	4
CAD	ST 100B	Cables	Boundary	4
LA Audio	DI 2	Active Direct Injection Box	Various	8
Klark Teknik	DN100	Active Direct Injection Box	Various	4

Radio microphones (Hire charges apply)

Make	Model	Detail / Accessories	Use	Total
Shure	UR4D	Clips, handheld transmitters (KSM9, Beta58A, and SM87C capsules available), bodypack transmitters (DPA 4066F Headset Mics Available)	Vocals and instruments	8

Audio Only Power

AUDIO ONLY distributed 240V with RCD Earth Leakage protection

FOH Position	x2	20 amp circuits.
	x1	16 amp Ceeform
DS: OP	x3	20 amp circuits.
DS: PS	x3	20 amp circuits.
Audio Booth	x3	20 amp circuits.
DS: PS	x1	30 amp 3 phase.
AMP Room	x1	63 amp 3 phase.
DS Prompt	x3	additional 32amp 3 phase.

House Speaker System

FOH Speakers

D&B V series line array in Left, Right, Centre, Sub and Fill configuration.

Array per side.

- 1 x V-sub at the top
- 6 x V8's
- 2 x V12's

Centre Array.

- 4 x Y12's

1 x B2 sub under each array.

1 x Y7p each side for in-fill.

6 x E8's along front edge of stage for front fill

(Note: The E8's can be positioned in front of the stage if required (e.g. for dance performances or shows designed for young children where placing them on top of the stage might present a sight line issue,

4 x additional V-sub for FOH or Monitoring applications.

Control & Amplification

Control

3 x Lake LM44, integrated signal processors with parametric EQ and time-alignment settings for system.

Dante signal distribution with a 6 x Redundant AES pairs from sound hold in the auditorium.

NB: (House EQ and time-alignment settings may be altered with EQ Layer on request.)

Amplifiers

7 x D&B D80 Amplifier Running Array processing

1 x D&B D20 Amplifier

(Note: The amplifiers listed above run the front of house system and are not available for other purposes).

Foldback

D&B M4 wedges x 16 with 4 x d80 amplifier rack (these allow up to 16 mixes when the amplifiers are running in passive mode, or 8 mixes when the amplifiers are running in active mode)

Meyer UM-1P x 8, 350w self powered, 45° x 45° 3' horn.

Note: Foldback systems are shared across venues. Please check on availability.

Locally available additional Hires.

Digidesign/Avid Profile, Digidesign/Avid SC48, Avid s6L Yamaha Pm5d, Midas Pro 2, Midas Pro 9, Midas Pro X, Soundcraft Vi Series Consoles, Digico SD10, Shure and Sennheiser In-Ear Monitor systems.

Audio Notes

- Microphone inventory is shared between Canberra Theatre and The Playhouse. Please check for availability.
- 3 x Lake LM44 processors are used on FOH and may be configured with up to 8 discrete inputs for Left, Right, Left Fill, Right Fill, Left Sub, Right Sub, Centre and Front Fill. Settings are also in place to run the entire system from a L&R signal input if required.
- Please note that microphone inventory, mixing consoles, projectors and screens are shared between venues, please ask for availability.
- As standard, the sound hold (X&Y 20-27) measures 4m x 1.7m deep.
- W+X+Y 20-27 measures 4m x 2.55m
- W+X+Y 16-27 measures 6m x 2.55m

AUDIO VISUAL

Projection Room

NA

Projectors

(Not inclusive of standard rig, hire charges apply)

Type	Model	Detail / Accessories	Total
Epson	EB-L1505UHNL	12k Laser Projector, various lens options + rigging frame	1
Barco	RLM.W6	3 x DLP chip, 6k ansi Lens 0.77:1, 1.4-1.77:1 Zoom Rigging frame	1
CTC		1.8m Projector stand on wheels	2

Screens

(Not inclusive of standard rig, hire charges apply)

Projection Screen

Type	Model	Detail / Accessories	Total
Nova	Rear pro	9'x12'	2
Nova	Front pro	9'x12'	1
Nova	Fast-fold	Surface frame	2
Stumpfl	VarioLock 64 Black 16:9	16' x 9' front or rear project screen. Black anodised frame, with legs for free standing option. Inc rigging brackets.	1

Nova screens can be flown from any convenient fly line.

Additional LED Screens (Not inclusive of standard rig, hire charges apply)

Type	Model	Detail / Accessories	Total
Samsung	DE55A	55" LED professional panel	2
Bigcity	Bigcity	2m stands	2

Cyclorama can be used for front or rear projection. Inclusive of standard rig

AV Playback Equipment

Item	Model	Detail / Accessories	Total
DVD/Blu-ray player	LG UBK90	4K Blu-ray/DVD Player	2
Laptop	Apple Macbook Pro with QLab 3	Various mini display port adapters (note: this laptop only has one video output)	1
Laptop	Apple Macbook Pro with QLab 4	USB-C Outputs with HDMI and USB-A adaptors (multiple video outputs)	1

AV Switching Equipment

Item	Model	Detail / Accessories	Total
Video Switcher	Blackmagic Design Television Studio	4 x HDMI Inputs, 4 x SDI Inputs, 1 x HDMI Program Output, 1 x SDI Program Output, 1 x SDI Aux Output, 1 x HDMI Multiview Output. Maximum output resolution: 1920 x 1080P	2

Projector Rigging Points

Projector cradles can be rigged from any available horizontal bar or fly line.
1.8m projector stand.

Cabling

SDI is the preferred delivery format with various lengths and patch points available.
Limited stock of VGA cable and interconnection available.
Composite VDA's and monitors available.

Audio Visual Notes

- Screens, projectors, and playback devices are shared between venues. Please check availability.
- SDI/Composite links available between FOH mixing position and stage.
- Cat 6a links available between FOH mixing position and stage.
- Composite video link between bio box and stage is available.
- Limited amounts of video links are available from prompt corner to various areas in the theatre.
- Wall mounted projector bracket fixed on rear wall. 8m from back wall to Cyclorama.
- 14m from orchestra bar to Cyclorama.
- Front projection is difficult from within the auditorium due to the angle required to clear the proscenium arch. As such it usually requires motors and a truss line to be rigged in the auditorium.

BACKSTAGE

Communications

Stage Managers Desk

SM console prompt corner, movable, light and phone

Talkback – Wired

Master Unit	Clearcom MS440, 4 loops
Total sub stations	12
Total headsets	12 Beyer DT109/108

Talkback patching located at

- Fly Rail O/P DS and US
- P/s corner (master unit)
- FOH position
- Bio box
- SM console
- P/S midstage
- Production desk (auditorium)
- Follow spot positions

Talkback – Wireless

Master Unit	Clear-Com FreeSpeak II
Total sub stations	6
Total headsets	6

Paging / Show relay

Paging to the dressing rooms and Green room is available from the stage managers desk. Show relay is distributed to all dressing rooms and green room. Dressing rooms 1 & 2 have individual volume controls.

Stage Monitor

Green room, SM desk, dressing room corridors, bio box, tearoom, stage door, foyer, dressing room 1

Cue Light System

Leon Audio

16 channel master station (QLM16 Mk4)

10 x outstations (9 x QLS Mk4 and 1 x QLS-SM Mk4)

1 x relay outstation (QLR Mk4)

Note: Shared between venues. Ask for availability

Dressing Rooms

Dressing Room	Capacity	Toilets	Shower	Details
Dressing Room 1	1 +	Yes	Yes	'Star' room 1 with private wc & shwr
Dressing Room 2	2			Shared WC / SHWR Ground Floor
Dressing Room 3	4			Shared WC / SHWR Ground Floor
Dressing Room 4	4			Shared WC / SHWR Ground Floor
Dressing Room 5	5			Shared WC / SHWR Ground Floor
Dressing Room 6	4			Shared WC / SHWR Ground Floor
Dressing Room 7	33	Yes	Yes	Female Chorus First Floor
Dressing Room 8	17	Yes	Yes	Male Chorus First Floor
Dressing Room 9	3			Shared WC / SHWR First Floor
Dressing Room 10	3			Shared WC / SHWR First Floor
Dressing Room 11	3			Shared WC / SHWR First Floor
Dressing Room 12	4			Shared WC / SHWR First Floor

Laundry / Wardrobe

Washing Machines	1 x Maytag 7.5 kg, 2 x Fisher & Paykel 8.0 kg,
Dryers	1 x SpeedQueen 9.0 kg, 1 x Bosch 9.0kg 2 x Hoover 5.0 kg
Drying rooms	N/A
Iron / ironing board	2 x Singer steam Irons, 1 x Propress Steamer
Clothes racks	Dressing rooms built-in and 3 x mobile racks
Towels	Available on request

Production Facilities

Production Desk

Production desk set-up in the centre of stalls. Table accommodates 2 people. Talkback and VDU mimic of lighting desk output available.

Production Office

Production offices available on first floor level backstage.

Phone

Two digital and one analogue metered lines available in each office. Not available for DSL

Fax

One analogue line available as above.

Internet access

Wifi available, no DSL

Greenroom

Tea / Coffee facilities	tea / coffee available on request. Boiling water on-tap
Fridge	Yes
Microwave	Yes
Running water	Yes

Stage Door

Access

Stage Door is located on the Eastern side of the building, accessed from the laneway (Knowles Place). A Stage Door person will be rostered on for any period that a hirer requires access to the backstage area

ADDITIONAL FACILITIES & INFORMATION

Orchestral

Wenger music stands with clip-on lights available.
Wenger adjustable chairs available.
Both items are shared with other venues in the Centre.
Upright piano is available.
Steinway Grand is available for hire
Tuning charged at cost.

Rehearsal Space

Courtyard Studio, 10m x 15m, concrete base with timber and black Masonite floor. Booking required for use.

Staffing

Technical minimum staffing levels are
1 x Lighting, 1 x Mechanist, 1 x Audio and 1 x Stage Door person.

Venue Plans

Venue Plan Available

YES, hard copy at 1:50 can be mailed, or a PDF or VXW file emailed upon request. Plan is available for download on the Canberra Theatre Centre website

Venue Section Available

YES, hard copy at 1:50 can be mailed, or a PDF or VXW file emailed upon request. Plan is available for download on the Canberra Theatre Centre website.

Venue Information

The Canberra Theatre Centre has three venues available for hire:

The Canberra Theatre 1239 seats stalls only

The Canberra Playhouse 614 seats, stalls and two balconies

The Courtyard Studio has 92 seats available in two different configurations.

The Canberra Theatre Centre reserves the right to change its inventory and specifications from time to time.