

# CANBERRA THEATRE CENTRE

Canberra Theatre

***Venue Hire Information***

***Technical Specifications***

**Schedule 13**

Updated  
12/01/2021

**The information in the following document was true and correct at the time of printing**

**The Canberra Theatre Centre reserves the right to adjust its inventory and specifications  
without notice**

# Contents

STAFF CONTACTS.....	5
VENUE HIRE .....	6
SUMMARY OF CHARGES .....	6
Rental Charges Inclusion.....	6
Industrial Relations Fee .....	6
STAFF .....	7
Standard Front of House.....	7
Standard Technical .....	7
Standard Box Office .....	7
Merchandise/Program Sales.....	7
STAGE .....	8
Auditorium.....	8
Orchestra Lift / Pit.....	9
Flying Facilities.....	9
Hanging Plot.....	10
Access Equipment.....	11
Lifting Equipment.....	12
Stage Covers .....	12
Loading Dock.....	12
Additional Rigging Notes .....	13
Staging Notes.....	13
LIGHTING .....	14
Positions.....	14
Control .....	14
Dimmer Systems .....	15
House Lights.....	15
Stage Luminaires.....	16
Followspots.....	17
Patching .....	17
Power .....	18
Cabling .....	18
Atmospherics .....	18
Lighting Notes.....	18

AUDIO.....	19
Control Points .....	19
Stage systems .....	20
Digital Audio Consoles .....	20
Microphones.....	21
Audio Only Power .....	22
House Speaker System .....	22
Control & Amplification .....	23
AUDIO VISUAL .....	24
Projectors.....	24
Screens.....	24
Audio Visual Notes.....	25
BACKSTAGE.....	26
Communications .....	26
Dressing Rooms .....	27
Laundry / Wardrobe .....	27
Production Facilities .....	27
Greenroom .....	28
Stage Door .....	28
ADDITIONAL FACILITIES & INFORMATION .....	28

## STAFF CONTACTS

### Technical Director

Phone Number: 02 6243 5736  
Mobile Number: 0420 578459  
Email Address: rohan.cutler@act.gov.au

### Rohan Cutler

### Technical Producer

Phone Number: 02 6243 5780  
Mobile Number: 0415 938 330  
Email Address: roni.wilkinson@act.gov.au

### Roni Wilkinson

### Head of Lighting

Phone Number 02 6243 5734  
Mobile 049717459  
Email Address stefan.wronski@act.gov.au

### Stefan Wronski

### Head Mechanist

Phone Number 02 6243 5758  
Mobile 0411 892542  
Email Address loki.clarke@act.gov.au

### Loki Clarke

### Head of Audio

Phone Number 02 6243 5759  
Mobile 0417 015644  
Email Address petar.milinkovic@act.gov.au

### Petar Milinkovic

### Box Office Manager

Phone Number 02 6290 9377  
Email Address sam.hardiman@act.gov.au

### Sam Hardiman

### Head of Programming

Phone Number 02 6243 5708  
Email Address gill.hugonnet@act.gov.au

### Gill Hugonnet

### Head of Marketing

Phone Number 02 6243 5706  
Email Address Adriana.law@act.gov.au

### Adriana Law

### Front of House Manager

Phone Number 02 6243 5766  
Email Address carole.arulantu@act.gov.au

### Carole Arulantu

### Stage Door

Phone Number 02 6243 5746 (Manned as required)

Venue Address	<b>Canberra Theatre Civic Square London Circuit Canberra ACT 2601</b>
Venue Postal Address	<b>Canberra Theatre Centre PO Box 226 Canberra ACT 2601</b>
Website:	<a href="http://www.canberratheatrecentre.com.au">www.canberratheatrecentre.com.au</a>

## VENUE HIRE

### SUMMARY OF CHARGES

Where the first performance date is more than 6 weeks out, a holding deposit of 50% of total rental is due on signing of contract, with the balance due 6 weeks before the first performance.

Where the first performance date is less than 6 weeks out, the full rental deposit is required.

**Note:** the venue booking is not secure and tickets will not go on sale until the contract and full deposit are received. Failure to provide full deposits within due dates will mean the automatic release of dates held and/or loss of partial deposit. Please see clause 13, page 11, of the Venue Hire Contract for cancellation

### Rental Charges Inclusion

One clean per day/performance (**Sunday and Public Holidays use will incur additional cost**)

Use of stage

Auditorium, Green Room, wardrobe and dressing rooms

Core management services, includes electricity and air conditioning.

**Note: All other costs incurred will be charged in addition to the rental rate.**

### Industrial Relations Fee

Per Performance as determined by L.P.A. Currently \$179.00

## STAFF

(per performance) (Penalty wages on Sundays and Public Holidays)

### Standard Front of House

8 x Ushers  
Program Sellers/Merchandisers (as required)  
1 x F.O.H. Manager  
Security (as required)

**Note:** *Variations to the above levels, for operational and/or safety reasons, are at the discretion of the FOH Manager*

### Standard Technical

1 x Electrician  
1 x Mechanist  
1 x Audio Technician  
1 x Stage Doorman

**Note:** *Variations to the above levels, for operational and/or safety reasons, are at the discretion of the Technical Director.*

### Standard Box Office

2 x Booking clerks

**Note:** *Variations to the above levels, for operational and/or safety reasons, are at the discretion of the Box Office Manager.*

All time worked on behalf of the Presenter, including overtime, penalty rates, minimum calls and on-costs, will be charged to the Presenter.

Cleaners will be charged to the Presenter for work on Sundays and gazetted holidays.

**Presenters unfamiliar with current award conditions and penalty rates are strongly advised to contact the Technical Director for further information.**

### Merchandise/Program Sales (per performance)

10% Gross Sales of audio visual material, plus seller's wages

15% of Gross Sales of all other materials, plus seller's wages

**Note:** *Merchandise and programs will be sold by Canberra Theatre Centre staff. Please see clause 8, page 9, of the Venue Hire Contract.*

## STAGE

### Brief Stage Description

Unraked stage with a proscenium arch and flying facilities. Hardwood floor covered with Masonite sheets. Screwing into surface permitted but larger holes to be authorised by Head Mechanist. Stage crossover behind US fly line.

Stage distributed load limit	<b>500kg/m2</b>
Stage point load limit	<b>Not Known</b>
Stage rake	<b>No</b>

### Stage Dimensions

#### Proscenium

Width	<b>16.9m</b>
Height	<b>5.8m</b>

#### Setting Line

**In line with House Curtain**

#### Distance From (*SL = Setting Line, CL = Centre Line*)

SL to US edge of fire curtain	<b>0.3m</b>
SL to DS edge of apron	<b>2.1m</b>
SL to DS edge of Orchestra Lift/Pit	<b>6.1m</b>
SL to first fly line	<b>220mm</b>
SL to last upstage fly line	<b>10.2m</b>
SL to rear wall	<b>18m</b>
CL to OP wall (or obstruction)	<b>9.8m</b>
CL to PS wall (or obstruction)	<b>18m</b>
Stage to underside of grid	<b>15.7m</b>

#### Overhead obstructions

**Fixed platforms at 7.2m above stage level between 400mm and 1m US of setting line, protruding onto stage at 6.95m from the centre line. Platforms are fixed on both sides of stage. Total distance between the platforms measures 13.9m**

## Auditorium

**Raked single level with central crossover.**

Seating capacity with additional Orchestra lift/pit seating installed	<b>1239</b>
---	-------------

Seating capacity <u>without</u> Orchestra lift/pit seating installed	<b>1184</b>
--	-------------



## Orchestra Lift / Pit

### Orchestra Lift

A motorised orchestra lift is operational

Set positions for orchestra lift where lift at auditorium level is 0mm

Stage level at **+1000mm** above auditorium.

Orchestra pit level at **-1400mm** below auditorium.

Lift can be set at any height? **Yes - pending CTC approval**

SWL of orchestra lift **3.5 Tonne**

Dimensions of the orchestra pit **4.2m x 15m**

Orchestra pit maximum capacity **45 – 50**

Pit net available **Yes**

**Standard pit position is at auditorium level with seating installed**

## Flying Facilities

### Fly System

**Single purchase handline system.**

### Fly System Details

Operating Position	<b>OP at stage level.</b>
Total number of Lines	<b>62</b>
Panorama Lines	<b>2 bars OP, 2 bars PS, electrically winched.</b>
Batten Drift	<b>14m</b>
Batten Type	<b>75x50mm batten.</b>
Batten Length	<b>16m</b>
Batten Extensions	<b>N/A</b>
Batten Pick-ups	<b>4 Pick ups</b>
Batten Point Load	<b>Not Known</b>
Batten W.L.L.	<b>500 kg</b>
Cradle Capacity	<b>340 kg</b>
LX bars can be swung	<b>Yes</b>
Fly bars can be swung	<b>No</b>

*SEE HANGING PLOT FOR LINE ALLOCATIONS AND FURTHER INFO*

## Hanging Plot

SL: Setting Line as indicated previously

Line Type: **SP** = Single purchase, **DP** = Double purchase, **MW** = Motor Winch, **HW** = Hand Winch, **HL** = Handline

S.W.L. = Maximum capacity above bar weight

Line #	Distance from SL	Line Type	S.W.L	Venue Allocation	Intended Use <i>(hiring company use)</i>
HC	0	MW		House Curtain	
1	220	SP	340kg	Pro Border	
2	370	SP	"	Pro Legs	
3	530	SP	"		Short batten to accommodate platforms. 13m length
4	700	SP	"	LX 1	Short pipe to accommodate platforms. 13m length
5					Not available for use
6					Not available for use
7	1150	SP	"		
8	1300	SP	"		
9	1440	SP	"		
10	1600	SP	"		
11	1750	SP	"		
12	1900	SP	"		
13	2050	SP	"		
14	2200	SP	"		
15	2360	SP	"		
16	2500	SP	"	Border	
17	2650	SP	"	Legs	
18	2800	SP	"		
19	2950	SP	"	LX 2	
20	3120	SP	"		
21	3270	SP	"		
22	3420	SP	"		
23	3570	SP	"		
24	3730	SP	"		
25	3880	SP	"		
26	4050	SP	"	Mid Tabs	
27	4200	SP	"		
28	4350	SP	"	Border	
29	4500	SP	"	Legs	
30	4650	SP	"		
31	4800	SP	"	LX 3	
32	4950	SP	"		
33	5100	SP	"		
34	5250	SP	"		
35	5450	SP	"		
36	5600	SP	"		
37	5750	SP	"		
38	5900	SP	"		
39	6050	SP	"		
40	6200	SP	"	Border	

41	6350	SP	"	Legs	
42	6500	SP	"		
43	6650	SP	"	LX 4	
44	6800	SP	"		
45	6950	SP	"		
46	7100	SP	"		
47	7250	SP	"		
48	7420	SP	"		
49	7560	SP	"		
50	7720	SP	"		
51	7880	SP	"		
52	8020	SP	"	Border	
53	8180	SP	"	Legs	
54	8350	SP	"		
55	8550	SP	"	LX 5 Flood Bar	
56	8800	SP	"		
57	8950	SP	"		
58	9100	SP	"		
59	9250	SP	"		
60	9400	SP	"		
61	9600	SP	"		
62	9800	SP	"	Smother	
63	10000	SP	"		
64	10200	SP	"	Cyclorama	

## Draperies

*Type	Material	Colour	Width	Height	Quantity
House Curtain	Velour	Blue/Grey	18m	6.9m	1
Borders	Flat Wool	Black	16m	3m	5
Legs	Flat Wool	Black	4m	7.3m	5
Tabs	Flat Wool	Black	16m	7m	2
Smother	Flat Wool	Black	16m	7m	1
Cyclorama	Plastic	Cream white	16.5m	8.2m	1
Scrim	Sharks tooth	Black	16m	6.7m	1
Scrim	Sharks tooth	White	16m	6.7m	1
Panorama Tabs	Flat Wool	Black	10m	10m	2

## Access Equipment

### Elevated Work Platform

Genie GS-1932, operator driven.

Upright UL-40DC, push around vertical lift.

Tallescope wheeled ladder. 90kg capacity.

**Max. platform height 5.8m**

**Max. platform height 12.2m**

**Max. platform height 5.9m**

**Please note the UL-40DC and tallescope units are shared between venues**

### EWP Restrictions

Outriggers must be used on the Uprights UL-40, and one staff member must be located at the base whilst in use.

## Ladders

- 1 x 0.9m aluminium stepladders
- 1 x 1.8m aluminium stepladders
- 1 x 1.8m fibreglass stepladder
- 1 x 3m aluminium stepladder
- 1 x 4.51m x 7.87m aluminium extension ladder.

## Staging Units

30 timber rostra with metal scissor action adjustable legs. 1000 x 2000 with height adjustable in 200mm increments. (i.e., 200mm, 400mm, 600mm, 800mm, 1000mm)

## Lifting Equipment

4 x 1tonne chain motors and control shared between both venues. There is an additional charge for these items, please contact Head Mechanist for pricing and availability.

## Stage Covers

<b>Style</b>	Tarkett: Harlequin 'Cascade'
<b>Dimensions</b>	6 rolls of 2m x 15m
<b>Colour</b>	Black

## Stage Traps

N/A

## Safety Curtain

Safety Curtain installed	<b>Yes</b>
Safety Curtain must be unobstructed at all times	<b>Yes</b>
Thickness of Fire Curtain	<b>200mm</b>
Distance from setting line	<b>300mm DS</b>

*Note: Measurement is to the downstage edge of the Fire Curtain.*

### Additional Requirements

Curtain must remain in the down position whilst venue not in use.

## Loading Dock

### Access

**Truck access via back laneway. Entry to this laneway is via the Northern car park at the rear of the Canberra Playhouse (Theatre Lane).**

Loading Dock Height	<b>Street level</b>
Door Dimensions	<b>4.5m High</b>
	<b>4.0m Wide</b>

### Restrictions / Obstructions

**Unloading/loading ramp required. Ramp required if equipment cannot be unloaded with a forklift.**

## **Additional Rigging Notes**

Rigging points O.P. and P.S. of orchestra LX bar 500kgs W.L.L.

For further information regarding the weight loading for rigging points over the stage and auditorium, please do not hesitate to contact the Head Mechanist.

The Head Mechanist is only too pleased to answer any questions with regards to rigging.

## **Staging Notes**

All flown items must be rigged with rated equipment and is subject to approval by a venue representative.

There is limited rigging gear available in house. Including lifting straps, FSWR lines, shackles and some pulleys.

Forklift and licensed operator available onsite.

# LIGHTING

## Positions

Stage LX Bars	All Stage LX bars except for LX 1 can be swung
	<b>LX1 Usable bar width</b> <b>12m</b>
	<b>All other LX bars usable bar width</b> <b>13m</b>

See hanging plot for standard LX bar locations

### FOH Orchestra Bar

Setting Line to lighting bar	<b>3.8m @ centre, curved to 2.5m at each end</b>
Usable bar width	<b>16m</b>

### FOH Concert Bar

Setting Line to lighting bar	<b>10.5m</b>
Height above Stage	<b>8.5m</b>
Usable bar width	<b>5.4m</b>

### FOH Bridge #1

Setting Line to lighting bar	<b>15.0m</b>
Height above Stage	<b>9m</b>
Usable bar width	<b>18.6m</b>

### FOH Box Booms (PS & OP)

Setting Line to FOH Box	<b>6.5m</b>	<i>(Distances are to the highest downstage point of boom or perch.)</i>
Maximum lanterns per box	<b>8</b>	

See Venue Plans for further information

## Control

Available Positions	<b>Control Room, Auditorium, Stage</b>
Lighting console	<b>ETC Gio 8k</b>
Output Parameters	<b>8192 (full spec at <a href="http://www.etcconnect.com">www.etcconnect.com</a> )</b>
LD Monitor	<b>Multi screen LD interface</b>
Signal output	<b>DMX 512 (as standard), ArtNet, ETCNet3</b>
Signal distribution	<b>Ethernet Spine, PathPort DMX nodes</b>
Wireless Remote riggers available	<b>Yes</b>

### Other consoles available on request:

- 1 x Martin M1 HD
- 1 x ETC Ion

## Dimmer Systems

<b>Total Dimmers</b>	<b>373</b>
2.5Kw Dimmer Racks	<b>State Automation SPC/APC/VST</b>
Total dimmers @ 2.5kw per dimmer	<b>333</b>
5Kw Dimmer Racks	<b>State Automation APC</b>
Total dimmers @ 5kw per dimmer	<b>40</b>

### Dimmer Locations

Dimmer outlets are distributed throughout the venue. Patch distribution plan available on request.

Several DMX controlled relay modules are available. These may be installed in any location within the dimmer system.

## House Lights

Independent control	<b>Yes. With adjustable fade time.</b>
Control positions	<b>Control Room, Prompt Corner, Auditorium Mix Position.</b>

## Stage Luminaires

### Profiles

Make	Model	Angle	Detail / Accessories	Watt	Numbers	Totals
ETC	Source 4	10	Rigged FOH bridge 4	750	6	6
ETC	Source 4	19	Rigged FOH Bridge 3 to give a 4 colour wash	750	24	40
ETC	Source 4	19	Rigged FOH Bridge 1 as specials	750	6	
ETC	Source 4	19	Store	750	10	
ETC	Source 4	15/30	Rigged FOH Box Booms to give a 4 colour wash	750	16	35
ETC	Source 4	15/30	Store	750	19	
ETC	Source 4	25/50	Store.	750	20	20
ETC	Source 4	26,36,50	Shared between venues. Contact HLX for availability.	750	40 Ea	40 Ea
Selecon	SPX Zoom	15/35	Rigged FOH Bridge 3 specials	800	6	40
Selecon	SPX Zoom	15/35	Rigged FOH Bridge 2 specials	800	8	
Selecon	SPX Zoom	15/35	Rigged 4 on each Stage LX bar specials	800	16	
Selecon	SPX Zoom	15/35	Store	800	10	
ETC	Source 4 Jr Zoom	25/50	6 on each stage perch and flown side ladders	575	60	80
ETC	Source 4 Jr Zoom	25/50	4 on each LX bar incl. Orchestra Bar (Break up gobo wash)	575	20	

### Fresnels

Make	Model	Detail / Accessories	Watt	Numbers	Totals
Selecon	Rama	Rigged Orchestra bar to give a 5 colour wash incl. o/w	1000	20	60
Selecon	Rama	Rigged 5 on each LX bar for an o/w wash	1000	20	
Selecon	Rama	Store	1000	20	
Selecon	Arena	Rigged 8 on each LX bar to give a 4 colour wash (High side cross)	2000	32	40
Selecon	Arena	Store	2000	8	
		Barn doors available for all the above.			

### PCs

Make	Model	Detail / Accessories	Watt	Numbers	Totals
Selecon	Rama	Store. Barn doors available.	1000	20	20

### Par Cans

Make	Model	Angle	Detail / Accessories	Watt	Total
Generic	PAR 64	MFL	240V	1000	24*
* Please check with the Head Electrician for availability as these lamps are no longer manufactured					

### CYC Wash

Make	Model	Detail / Accessories	Watt	Numbers	Total
Altman	Spectra CYC200	LED RGBA 10 channel Flood Bar (line 55)	480	7	20
Altman	Spectra CYC200	LED RGBA 10 channel Ground Row	480	7	
Altman	Spectra CYC200	Store	480	6	
Ianaro	Pallas 4 cell	Store	750	16	16
Selecon	Cyc 4 cell	Store	800	10	10



## Followspots

Make	Model	Angle	Detail / Accessories	Watt	Total
Selecon	Performer	5/9	6 colour magazine	1200	2
Robert Juliat	Aramis	4.5/8	6 colour magazine + CTO + Frost Mechanical dimmer	2500	2

## Additional Lighting

Item	Make	Model	Detail / Accessories	Watt	Total
Intelligent luminaires	Robe	<a href="#">Robin 800 wash</a>	Shared between venues	LED 700	16
	Robe	<a href="#">DL4X spot</a>	Shared between venues	LED 700	8
2 way LED Molefay	ShowPro	<a href="#">Blinder II</a>	Shared between venues	LED 156	4
4 way LED Molefay	ShowPro	<a href="#">X-Blinder</a>	Shared between venues	LED 300	4
RGBW LED Par	Martin	<a href="#">Rush Par 2</a>	Shared between venues	LED 152	22

## Patching

Location	Quantity	Numbering	Detail / Accessories
Rear FOH			CCT bar 8 circuits to Concert Bar Patch
PS FOH Bridge 1			CCT bar 12 circuits to Concert Bar Patch
CS FOH Bridge 1			CCT bar 12 circuits to Concert Bar Patch
OP FOH Bridge 1			CCT bar 12 circuits to Concert Bar Patch
CS Concert bar	43	1 – 43	CCT bar 16 circuits to Concert Bar Patch
CS FOH Orchestra bar	18	44 – 61	CCT bar 40 circuits to Orchestra Bar Patch
PS FOH Box boom	8	62 – 69	
OP FOH Box boom	8	70 - 77	
PS Pit Wall	1	78 - 84	
OP Pit Wall	1	85	
PS Fly Floor		86 - 229	Flown Spot bars numbered from D/S 222 – 229 20Amp sockets 1 x 20Amp hot power US
PS Lighting Bridge	20	230- 249	230 – 237 paired with Perch bar on tormentor
PS DS above floor	4	250 - 253	Situated low to the stage floor (not a well)
OP Lighting bridge	20	254 - 273	254 – 261 paired with Perch bar on tormentor
OP DS above floor	4	274 - 277	Situated low to the stage floor (not a well)
OP fly floor US	10	278 - 287	
US OP wall	6	288 - 293	
PS Stage Floor Wells	30	294 - 323	5 wells – 6 per well
OP Stage Floor Wells	30	324 - 353	5 wells – 6 per well
US PS Stage Well	4	354 - 357	20 Amp sockets -1 x 20Amp hot power
US OP Stage Well	4	358 - 361	20 Amp sockets - 1 x 20Amp hot power
US PS Fly floor	8	362 - 369	4 x 10 Amp sockets per dimmer 6m above stage level
Rear wall	4	369 - 373	20 Amp sockets

## Power

### 3 Phase Outlets

- 3 x 40 amp 3phase outlets DS PS (8m from acting area)
- 3 x 40 amp 3phase outlets US OP (5m from acting area)
- 2 x 40 amp 3phase outlets US OP Basement (10m from Orchestra Pit)
- 2 x 40 amp 3phase outlets PS fly floor (6m above stage level)

### Power Lock

- 100 amp 3 phase supply available on PS Fitted with Power Lock sockets (other wiring formats require licensed electrician to wire in)
- 250 amp 3 phase supply available on OP Fitted with Power Lock sockets (other wiring formats require licensed electrician to wire in)

## Cabling

### 240v Extension Cable

- 100 x 10m
- 50 x 7m
- 50 x 5m

### Looms

- 10 x 4-way at 15m

### 3 phase Extensions

- 4 x 20m Shared between venues.

## Atmospherics

- |                                    |   |
|------------------------------------|---|
| 1 x MDG ATMe haze machine          | <b>DMX and stand-alone function available</b> |
| 1 x Rosco 1600 fog machine *       | <b>DMX and stand-alone function available</b> |
| 2 x Martin Jem Compact Hazer Pro * | <b>DMX and stand-alone function available</b> |

*Please note there is an additional hire charge associated with these products. Please contact the Head of Lighting for more information*

*\*These products are shared between venues. Please check with Head of Lighting for availability*

## Lighting Notes

- FOH standard rig gives an excellent front 4-colour wash
- 10 x 2m five rung wheeled floor ladders available (1 lantern per rung)
- The ladders are extendable to 4m with attachable pipe.
- On stage spot bars have 24 circuits each and are generally 13m in length

# AUDIO

## Control Points

Control Room	<b>Yes</b>	
Location Detail	<b>Bio box</b>	<b>2.5m x 2m</b>
Tie Lines to stage	<b>Yes</b>	<b>x 20</b>
Auditorium	<b>Yes</b>	
Location Detail	Centre mid rear	

## Default hold

Seats X, Y 16-27, W 20-27 and ZA 16-26.

Row W is held for to accommodate console overhang.

Row ZA is held if sightlines are impaired over the console

**6m x 1.7m** (X&Y 16-27). **Total 43 seats**

## Typical hold

Seats X, Y 20-27 and ZA 21-24.

Row ZA is held if sightlines are impaired over the console.

**4m x 1.7m** (X&Y 20-27). **Total 16-20 seats**

## Sound hold Connections to prompt corner.

- **36** x analogue male XLR inputs from prompt corner.
- **16** x analogue female XLR feeds to prompt corner.
- **4** channels of coms connections to SM console.
- **6** lines of cat 6A to prompt corner.
- **4** lines of rg56 suitable for SDI, MADi and AVID connections to prompt corner.

## Cross stage Audio patch Prompt to OP corner.

- **20** x XLR line 16 male and 4 female at prompt end.
- **2** x cat 6A lines.
- **2** x SDI/MADI lines.

## Up stage Audio patch Prompt to back stage centre.

- **4** x cat 6A lines.
- **2** x SDI/MADI lines.
- **2** x analogue XLR lines.

## Stage systems

### Radial Engineering 56-Channel Convertible V12 Snake System

- 56 x XLR inputs
- 3 x outputs (1 x Direct, 2 x Transformer Isolated) with cables (XLR Tails)
- 5 x 12-Way input patch
- 10 x 12-input stage boxes
- 5 x 15 metre sub-snakes
- 5 x 30 metre sub-snakes

*Additional sub-snakes and stage boxes may be available on request*

### Multicore hard-wired stage drops

- 1 x 20m (8 XLR Male Tail to 8 XLR Female Stage Box)
- 1 x 20m (12 XLR Male Tail to 12 XLR Female Stage Box)
- 1 x 30m (8 XLR Male Tail to 8 XLR Female Stage Box)
- 1 x 30m (12 XLR Male Tail to 12 XLR Female Stage Box)

### Cables

XLR Cables (Various lengths- please advise quantity required)

Note: Stage systems and cables are shared across venues. Please check on availability.

## Digital Audio Consoles

**DiGiCo consoles.** See <http://www.digico.biz/>

DiGiCo SD8 (Stealth Core 2, software version 12.2.1280) + **Madi-Rack** (48 Inputs + 16 Outputs. Note: Madi-Rack is limited to 48kHz Operation)

DiGiCo SD9 (Stealth Core 2, software version 12.2.1280) + **D-Rack** (32 Inputs + 8 Outputs)

DiGiCo SD11 (Stealth Core 2, software version 12.2.1280) + **D-Rack** (32 Inputs + 8 Outputs)

**Yamaha consoles.**

See <http://www.yamahaproaudio.com/global/en/products/mixers/>

Yamaha M7CL-32

Yamaha DM1000

Note: Mixing consoles are shared across venues. Please check on availability.

## Playback

Item	Make	Model	Detail	Total
CD player	Denon	DN-C680	Single CD player	2
MD player	Denon	DN-M1050R	Single Minidisc player/recorder	2
File player	Denon	<a href="#">DN-F650R</a>	USB/SD wav/mp3 recorder/player	1
USB DI	ARX	USBDI	Computer USB audio interface	2
USB DI	Radial	USB-Pro		2

## Accessories

Item	Model	Detail / Accessories	Total
Microphone stands	Round base	Straight	8
Microphone stands	Tri base	Boom arm tall	24
Microphone stands	Tri base	Boom arm short	16

## Speaker Patching

Location	Quantity	Numbering	Detail
Redundant speaker patching available on XLR	12	NA	PC to various stage points

## Microphones

Make	Model	Detail / Accessories	Use	Total
Shure	Beta 87A	Clips	Vocals	4
Shure	Beta 58A	Clips	Vocals	6
Shure	SM58	Clips	Vocals	2
Shure	SM58S	Switched	Shout/Announce	4
Shure	SM57	Clips	Instruments	8
Shure	Beta52A	Built-in stand adaptor	Drums, instruments	1
Shure	B91	all	Instruments	1
Shure	B98	all	Drums	4
AKG	CK93	Clips	Instruments	4
AKG	CK98	Clips	Distance miking	2
AKG	SE300B	Clips	Preamp for 93/98	6
AKG	C451B	Clips	Instruments	6
AKG	C414	Clips	Various	4
Neumann	KM184	Clips	Instrument	8
Beyer	M88	Clip	Instrument	1
Sennheiser	E604	Claw	Percussion	4
Sennheiser	E906	Clips	Instrument	2
Sennheiser	MD421	Clips	Instrument	4
Audix	D6	Clips	Kick drum	2
Audio Technica	AE2500	Clips	Kick Drum	1
Crown	PCC160 PZM	-	Boundary	4
CAD	ST 100B	Cables	Boundary	4
LA Audio	DI 2	Active Direct Injection Box	Various	8
Klark Teknik	DN100	Active Direct Injection Box	Various	4

## Radio microphones (Hire charges apply)

Make	Model	Detail / Accessories	Use	Total
Shure	UR4D	Clips, handheld transmitters (KSM9, Beta58A, and SM87C capsules available), bodypack transmitters (DPA 4066F Headset Mics Available)	Vocals and instruments	8

## Audio Only Power

AUDIO ONLY distributed 240V with RCD Earth Leakage protection

FOH Position	x2	20 amp circuits.
	x1	16 amp Ceeform
DS: OP	x3	20 amp circuits.
DS: PS	x3	20 amp circuits.
Audio Booth	x3	20 amp circuits.
DS: PS	x1	30 amp 3 phase.
AMP Room	x1	63 amp 3 phase.
DS Prompt	x 3	additional 32amp 3 phase.

## House Speaker System

### FOH Speakers

**D&B V series line array** in Left, Right, Centre, Sub and Fill configuration.

#### Array per side.

- 1 x V-sub at the top
- 6 x V8's
- 2 x V12's

#### Centre Array.

- 4 x Y12's

1 x B2 sub under each array.

1 x Y7p each side for in-fill.

6 x E8's along front edge of stage for front fill

(Note: The E8's can be positioned in front of the stage if required (e.g. for dance performances or shows designed for young children where placing them on top of the stage might present a sight line issue,

4 x additional V-sub for FOH or Monitoring applications.

## Control & Amplification

### Control

**3 x Lake LM44**, integrated signal processors with parametric EQ and time-alignment settings for system.

**Dante signal distribution with a 6 x Redundant AES pairs from sound hold in the auditorium.**

*NB: (House EQ and time-alignment settings may be altered with EQ Layer on request.)*

### Amplifiers

**7 x D&B D80 Amplifier Running Array processing**

**1 x D&B D20 Amplifier**

**(Note: The amplifiers listed above run the front of house system and are not available for other purposes).**

### Foldback

**D&B M4 wedges x 16 with 4 x d80 amplifier rack (these allow up to 16 mixes when the amplifiers are running in passive mode, or 8 mixes when the amplifiers are running in active mode)**

**Meyer UM-1P x 8, 350w self powered, 45° x 45° 3' horn.**

**Note: Foldback systems are shared across venues. Please check on availability.**

## Locally available additional Hires.

Digidesign/Avid Profile, Digidesign/ Avid SC48, Avid s6L Yamaha Pm5d, Midas Pro 2, Midas Pro 9, Midas Pro X, Soundcraft Vi Series Consoles, Digico SD10, Shure and Sennheiser In-Ear Monitor systems.

## Audio Notes

- Microphone inventory is shared between Canberra Theatre and The Playhouse. Please check for availability.
- 3 x Lake LM44 processors are used on FOH and may be configured with up to 8 discrete inputs for Left, Right, Left Fill, Right Fill, Left Sub, Right Sub, Centre and Front Fill. Settings are also in place to run the entire system from a L&R signal input if required.
- Please note that microphone inventory, mixing consoles, projectors and screens are shared between venues, please ask for availability.
- As standard, the sound hold (X&Y 20-27) measures 4m x 1.7m deep.
- W+X+Y 20-27 measures 4m x 2.55m
- W+X+Y 16-27 measures 6m x 2.55m

## AUDIO VISUAL

### Projection Room

NA

### Projectors

(Not inclusive of standard rig, hire charges apply)

Type	Model	Detail / Accessories	Total
Epson	<a href="#">EB-L1505UHNL</a>	12k Laser Projector, various lens options + rigging frame	1
Barco	<a href="#">RLM W6</a>	3 x DLP chip, 6k ansi Lens 0.77:1, 1.4-1.77:1 Zoom Rigging frame	1
CTC		1.8m Projector stand on wheels	2

### Screens

(Not inclusive of standard rig, hire charges apply)

#### Projection Screen

Type	Model	Detail / Accessories	Total
Nova	Rear pro	9'x12'	2
Nova	Front pro	9'x12'	1
Nova	Fast-fold	Surface frame	2
Stumpfl	VarioLock 64 Black 16:9	16' x 9' front or rear project screen. Black anodised frame, with legs for free standing option. Inc rigging brackets.	1

*Nova screens can be flown from any convenient fly line.*

### Additional LED Screens (Not inclusive of standard rig, hire charges apply)

Type	Model	Detail / Accessories	Total
Samsung	DE55A	55" LED professional panel	2
Bigcity	Bigcity	2m stands	2

*Cyclorama can be used for front or rear projection. Inclusive of standard rig*

### AV Playback Equipment

Item	Model	Detail / Accessories	Total
DVD/Blu-ray player	LG UBK90	4K Blu-ray/DVD Player	2
Laptop	Apple Macbook Pro with QLab 3	Various mini display port adapters (note: this laptop only has one video output)	1
Laptop	Apple Macbook Pro with QLab 4	USB-C Outputs with HDMI and USB-A adaptors (multiple video outputs)	1

### AV Switching Equipment

Item	Model	Detail / Accessories	Total
Video Switcher	Blackmagic Design Television Studio	4 x HDMI Inputs, 4 x SDI Inputs, 1 x HDMI Program Output, 1 x SDI Program Output, 1 x SDI Aux Output, 1 x HDMI Multiview Output. Maximum output resolution: 1920 x 1080P	2



## **Projector Rigging Points**

Projector cradles can be rigged from any available horizontal bar or fly line.  
1.8m projector stand.

## **Cabling**

SDI is the preferred delivery format with various lengths and patch points available.  
Limited stock of VGA cable and interconnection available.  
Composite VDA's and monitors available.

## **Audio Visual Notes**

- Screens, projectors, and playback devices are shared between venues. Please check availability.
- SDI/Composite links available between FOH mixing position and stage.
- Cat 6a links available between FOH mixing position and stage.
- Composite video link between bio box and stage is available.
- Limited amounts of video links are available from prompt corner to various areas in the theatre.
- Wall mounted projector bracket fixed on rear wall. 8m from back wall to Cyclorama.
- 14m from orchestra bar to Cyclorama.
- Front projection is difficult from within the auditorium due to the angle required to clear the proscenium arch. As such it usually requires motors and a truss line to be rigged in the auditorium.

# BACKSTAGE

## Communications

Stage Managers Desk

SM console prompt corner, movable, light and phone

### Talkback – Wired

Master Unit	Clearcom MS440, 4 loops
Total sub stations	12
Total headsets	12 Beyer DT109/108

### Talkback patching located at

- Fly Rail O/P DS and US
- P/s corner (master unit)
- FOH position
- Bio box
- SM console
- P/S midstage
- Production desk (auditorium)
- Follow spot positions

### Talkback – Wireless

Master Unit	<b>Clear-Com FreeSpeak II</b>
Total sub stations	<b>6</b>
Total headsets	<b>6</b>

## Paging / Show relay

Paging to the dressing rooms and Green room is available from the stage managers desk. Show relay is distributed to all dressing rooms and green room. Dressing rooms 1 & 2 have individual volume controls.

## Stage Monitor

Green room, SM desk, dressing room corridors, bio box, tearoom, stage door, foyer, dressing room 1

## Cue Light System

### Leon Audio

16 channel master station (QLM16 Mk4)

10 x outstations (9 x QLS Mk4 and 1 x QLS-SM Mk4)

1 x relay outstation (QLR Mk4)

**Note: Shared between venues. Ask for availability**

## Dressing Rooms

Dressing Room	Capacity	Toilets	Shower	Details
Dressing Room 1	1 +	Yes	Yes	'Star' room 1 with private wc & shwr
Dressing Room 2	2			Shared WC / SHWR Ground Floor
Dressing Room 3	4			Shared WC / SHWR Ground Floor
Dressing Room 4	4			Shared WC / SHWR Ground Floor
Dressing Room 5	5			Shared WC / SHWR Ground Floor
Dressing Room 6	4			Shared WC / SHWR Ground Floor
Dressing Room 7	33	Yes	Yes	Female Chorus First Floor
Dressing Room 8	17	Yes	Yes	Male Chorus First Floor
Dressing Room 9	3			Shared WC / SHWR First Floor
Dressing Room 10	3			Shared WC / SHWR First Floor
Dressing Room 11	3			Shared WC / SHWR First Floor
Dressing Room 12	4			Shared WC / SHWR First Floor

## Laundry / Wardrobe

Washing Machines	<b>1 x Maytag 7.5 kg, 2 x Fisher &amp; Paykel 8.0 kg,</b>
Dryers	<b>1 x SpeedQueen 9.0 kg, 1 x Bosch 9.0kg 2 x Hoover 5.0 kg</b>
Drying rooms	<b>N/A</b>
Iron / ironing board	<b>2 x Singer steam Irons, 1 x Propress Steamer</b>
Clothes racks	<b>Dressing rooms built-in and 3 x mobile racks</b>
Towels	<b>Available on request</b>

## Production Facilities

### Production Desk

Production desk set-up in the centre of stalls. Table accommodates 2 people. Talkback and VDU mimic of lighting desk output available.

### Production Office

Production offices available on first floor level backstage.

### Phone

Two digital and one analogue metered lines available in each office. Not available for DSL

### Fax

One analogue line available as above.

### Internet access

Wifi available, no DSL

## Greenroom

Tea / Coffee facilities	<b>tea / coffee available on request. Boiling water on-tap</b>
Fridge	<b>Yes</b>
Microwave	<b>Yes</b>
Running water	<b>Yes</b>

## Stage Door

### Access

Stage Door is located on the Eastern side of the building, accessed via the laneway behind the ACT Legislative Assembly. A Stage Door person must be rostered on for any period that a hirer requires access to the backstage area

# ADDITIONAL FACILITIES & INFORMATION

### Orchestral

Wenger music stands with clip-on lights available.  
Wenger adjustable chairs available.  
Both items are shared with other venues in the Centre.  
Upright piano is available.  
Steinway Grand is available for hire  
Tuning charged at cost.

### Rehearsal Space

Courtyard Studio, 10m x 15m, concrete base with timber and black Masonite floor. Booking required for use.

## Venue Plans

### Venue Plan Available

YES, hard copy at 1:50 can be mailed, or a PDF or VXW file emailed upon request. Plan is available for download on the Canberra Theatre Centre website

### Venue Section Available

YES, hard copy at 1:50 can be mailed, or a PDF or VXW file emailed upon request. Plan is available for download on the Canberra Theatre Centre website.

## Venue Information

The Canberra Theatre Centre has three venues available for hire:

The Canberra Theatre 1239 seats stalls only

The Canberra Playhouse 614 seats, stalls and two balconies

The Courtyard Studio has 92 seats available in two different configurations.

**The Canberra Theatre Centre reserves the right to change its inventory and specifications from time to time.**